

WINDSOR

Phone: 5199668642
1885 Provincial Road
Windsor, ON
Email: mikeb@vehicleventure.com



2023 Cub Cadet PRO Z 560L KW Zero Turn Riding Lawn Mower

Stock#: 53TIHJUV050 VIN#: 53TIHJUV050 Year: 2023
Manufacturer: Cub Cadet
URL: <https://vehicleventure.com/2023-cub-cadet-pro-z-560l-kw-zero-turn-riding-lawn-mower--c00p.html>

Price	\$19,899.00
Sales Price	\$14,500.00

Description

EQUIPPED TO GET MORE DONE
Every part of the PRO Z 500 L was thoughtfully considered to maximize your work day. Bigger, faster engines and more fuel capacity means more cutting time and more acres mowed, every day.

BEST-IN-CLASS DECK
Stand up to the toughest conditions with the only commercial lawn mower touting a triple-7-gauge steel cutting deck made of 7-gauge top and bottom reinforcements, plus 1/4" leading edge and 5/16" side reinforcements.

CUT DOWN JOB TIME
Finish the job efficiently with a 60" cutting deck option and twin fuel tanks that have a 14.9 gallon capacity. The KohlerRegistered EFI engine can save up to 25% on fuel consumption, without compromising strength and power.

ALL-DAY COMFORT
Ride in comfort on the standard high-back suspension seat with an angle-adjustment dial and additional customization controls for the perfect fit. Oversized lap bars with an integrated automatic parking brake system reduce operator fatigue.

MAXIMIZE YOUR WORKDAY
Productivity-enhancing features optimize rear weight distribution, including pre-drilled mounting points for attachments and smart fuel pod placement.

MAINTENANCE-FREE SPINDLE
Slash downtime thanks to Cub Cadet's new spindle design. Completely sealed, dual double-row ball bearings make the spindle maintenance-free for its lifetime, and anti-friction washers prevent self-tightening, meaning easier blade maintenance.

PRO Z 560L KW

SPECIFICATIONS

STEERING

Lap Bar / Steering Wheel Adjustment

3/4 length padded bars w/toolless quick adjust dial

CHASSIS

Rear Bumper

5/16" Thick Steel rear engine guard/pre-drilled mounting points for attachments with integrated rear hitch

Front Axle / Yolks

2" x 3" solid axle tube and 1/2" thick steel front yokes

Frame

Fully welded, full-length 3/8 x 5" laser cut steel / integrated tie-down slots

ROPS

2" x 2" quick-latch tool-less foldable 3 position

OPERATION

Cruise Control

N/A

Throttle/PTO/Key Switch

HD Low-profile throttle lever, sealed key switch & electronic fingertip engagement pto

PTO Clutch

Warner PTO Clutch (200 ft. lb.) with Soft-Start

Lap Bar / Steering Wheel Control

High Performance & Speed Control

Seat Type

High-back dial suspension with EVC Cushion

seat belt

angle back adjust

arm rests

Front Tires

13" x 6.5" - 6" (smooth)

Park Brake / Braking

Hand-operated lever with integrated hydro pump release lever

Rear Tires

24" x 12" - 12" (Turf Tread)

MOWER DECK

Deck Size/Type
60" FABRICATED DECK

Top Reinforcement(s)
7ga. (.187") top plate

Spindle Construction
8" sealed cast aluminum housing (maintenance-free)

Discharge Chute
High-density, impact-resistant rubber

Leading Edge Reinforcement
1/4" (.250") steel

Side Construction
5/16"(.313) steel on trim and discharge sides

Bottom Reinforcement
7ga. (.187") bottom plate

Deck Material
fabricated 7ga. (.187") steel shell

Deck Height Adjustment
Foot pedal with spring assist
16 Positions

Trim-Side Wear Guard
3/4" Thick UHMW-PE Replaceable Trim-side Wear Guard

Cutting Height
1" - 5"

Rolled Leading Edge Reinforcement
1/4" (.250") steel

Deck Blades
3 high-lift MarbainRegistered blades / 18,500 fpm (approx.)

Anti-Scalping
2 Front HD w/ Bushings & Grease Zerk

Deck Style/Construction
7ga. top plate
7ga. bottom reinforcement
1/4" rolled leading edge

GENERAL

Cup Holder
Intergrated into Side Pod

Hour Meter
Standard electronic

WARRANTY

Warranty

3 year / no hour limit commercial warranty and 5 year / 1,750 hour limited deck construction warranty

Engine & Drive System

Ground Speed

Fwd: 10 mph/Rev: 5 mph

Engine Type

Kawasaki FX850v

Fuel Capacity

Twin 7.45 gal. tanks (14.9 gal. total) with dial gauge

Horsepower / CC's

27hp - 852cc

Transmission

Parker HTJ Series

12cc pump / 260cc wheel motor

DIMENSIONS

Weight (approx)

1324 lbs.

L / W / H with discharge chute UP and ROPs DOWN

84" L x 62" W x 50" H